

डॉ. बाबासाहेब आंबेडकर मराठवाडा विद्यापीठ, छत्रपती संभाजीनगर

नॅक समिती तर्फे 'अ+' दर्जा प्राप्त

ई.पी.ए.बी.एक्स. :- (०२४०) २४०३३९७ ते ४००
 कार्यालय दूरध्वनी :- (०२४०) २४०३१०४ ते १०६
 कुलसचिव (का). :- (०२४०) २४०३३३३
 कुलसचिव (नि). :- (०२४०) २४००२०३
 फॅक्स :- (०२४०) २४०३११३ / २४०३३३५
 तार :- बामुसिटी
 Web Site :- www.bamu.ac.in
 E-mail :- registrar@bamu.ac.in



विद्यापीठ परिसर,
 छत्रपती संभाजीनगर - ४३१ ००४
 (महाराष्ट्र)

संदर्भ क्र. युई/भांडार/२०२६-२७/ 625

दिनांक: २८/०७/२०२६
29

विषय: दरपत्रक सादर करणे बाबत.

महोदय,

वरील विषयास अनुसरून कळविण्यात येते की, स्थावर विभागात **Purchase of Furniture for Guest House Building at Sub-Campus Dharashiv** खरेदी/ सेवा / देखभाल दुरुस्तीसाठी खाली नमुद केलेल्या तांत्रिक बाबींची पूर्तता करून दि. 10/8/2026, रोजी दुपारी 5.30 PM वाजेपर्यंत दरपत्रक सादर करावेत.

Sr. No.	Name of the Article with Description or Specification	Qty.	Rate	Total Cost
1	3 + 1+ 1 Sofa set Size: 171 W x 81 D x 84 H cm Godrej Monarch 1 Seater sofa Size: 80 W x 81 D x 84 H cm Colour- Burgandy Syntic Leather	02		
2	Coffee Table Plywood Material size : 18 mm Color:- Sonama Oak Dimensions W x H x D (cm) - 45 x 47.1 x 90	02		
3	Corner Table Plywood Material size : 18 mm Dimensions W x H x D (cm) - 45 x 46.9 x 45 Color:- Sonama Oak	02		
	Reception Area			
4	Reception Table, Size:- 1500W X 725D X 740H Overall Height - 1080 H mm Specification:- Work Surface - Made of 25mm Thick Pre-laminated twin board of E1-P2 grade and approved shade confirming to IS-12823:1990, Edge banded with matching 2 mm thick PVC lipping. Access Flap provided on work surface for wire management. Wire Management - Power box made with 0.8 mm thick CRCA (IS: 513), with switch plate (8+3 Module cutout provision for Anchor Roma). This is fixed with worktop along the width at Access Flap position. Modesty Panel & Side Skirting - Made of 25mm Thick Pre-laminated twin board of E1-P2 grade and approved shade confirming to IS-12823:1990, Edge	01		

	banded with matching 2 mm thick PVC lipping. Understructure - Made of 18mm Thick Pre-laminated twin board of E1-P2 grade and approved shade confirming to IS-12823:1990, Edge banded with matching 2 mm thick PVC lipping. TOP shelf - Made of 18mm Thick Pre-laminated twin board of E1-P2 grade and approved shade confirming to IS-12823:1990, Edge banded with matching 2 mm thick PVC lipping. Hinge Door + Drawer unit Made of 18mm Thick Pre-laminated twin board of E1-P2 grade and approved shade confirming to IS-12823:1990, Edge banded with matching 2 mm thick PVC lipping. Drawer bottom is made of 5.5thk PLYWOOD MATERIAL whiteboard. Handle is provided for ease of opening. HDU and Drawer is provided with cam lock for security. Essential Accessories - Wire Riser made of 0.8mm CRCA (IS-513) is provided for proper wire management. Organizer Plate made of 1.2mm CRCA (IS-513) is provided for magnetic sticky notes. Bag Hanger Hook made of 1.2mm CRCA (IS-513) is provided for bag hanging.			
5	Mid Back Chair Specification:- SEAT/BACK ASSEMBLY: The seat made from 1.2 ± 0.1 cm. thk. hot pressed plywood and back should be injection moulded from black Co-polymer Polypropylene upholstered with fabric and moulded Polyurethane foam together with seat and back covers. The back foam should be designed with contoured lumbar support for extra comfort. SEAT SIZE: 45.0cm(W) x 42.0cm.(D) BACK SIZE: 39.0cm(W) x 38.0cm.(H) 2. SEAT / BACK COVERS: The seat and back covers should be injection moulded in black Co-polymer Polypropylene. 3. HIGH RESILIENCE (HR) POLYURETHANE FOAM : The HR polyurethane foam should be moulded with density = 45 ± 2 kg/m³ and Hardness load 16 ± 2 kgf as per should be :7888 for 25% compression. ARMREST ASSEMBLY: The one-piece armrests should be injection moulded from black Nylon. The armrests should be fitted to the seat with armrest connecting brackets made of 0.5 ± 0.05 cm. thk. HR steel. PERMANENT CONTACT mechanism: The permanent contact mechanism should be designed with the following features: 360° revolving type. $14^\circ \pm 2^\circ$ maximum back-tilt only Upright, position locking.. Tilt tension adjustment. 6. PNEUMATIC HEIGHT. ADJUSTMENT: The pneumatic height adjustment has an adjustment stroke of 11.0 ± 0.3cm. TELESCOPIC BELLOW ASSEMBLY: The bellow should be 3 piece telescopic type and injection moulded in black Polypropylene.PEDESTAL ASSEMBLY: The pedestal should be injection moulded in black 30% glass-filled Nylon and fitted with 5 nos.: twin wheel castors. The pedestal should be 62.0 ± 0.5cm. pitch-centre dia. (72.0 ± 1.0cm with castors). 9. TWIN WHEEL CASTORS: The twin wheel castors should be injection moulded in Black Nylon.	01		
6	Storwel Size:- 916mm(W)x486mm(D)x1981mm(H) Specifation:- Storwel Full Height shall have an overall size of 916mm (W)x486mm(D)x1981mm(H) with welded construction. It should have the shelf thickness of 0.7 mm, Back thickness of 0.8mm, Door thickness of 0.8mm (high yield strength) and all other components shall have a	01		


thickness of 0.9mm. These components shall be made of CRCA 'D' grade high yield strength as per IS:513. The Storwel Plain should have a Mazak handle and Three way locking mechanism with Shooting Bolts. It should have a height wise adjustable shelf mounting which shall have a Uniformly Distributed Load Capacity of max 40 Kg. It should also have a M10 Screw type Leveller with Hex plastic base. The finishing shall include Epoxy powder coated to the thickness of 50 microns (+/- 10). Plenty of colour options and shelving options shall be available.			
	Total Amount		

दरपत्रका सोबत खालील कागदपत्रे जोडणे आवश्यक आहे.

1. Copy of acknowledgement of Income Tax Return for last financial year
2. Copy of Registration Certificate / Shop Act. License Copy
3. PAN Card.
4. GST Registration.
5. Authorised Dealer / Sub Dealer

विशेष टिप्पणी :-

- दरपत्रके दोन लिफाफ्यात सादर करावीत १) एका लिफाफ्यात वरील प्रमाणे तांत्रिकबाबीसह उपरोक्त कागदपत्रे असावीत २) दुसऱ्या लिफाफ्यात फक्त दर नमूद केलेले असावेत (दर सर्वकरांसहीत नमूद करावेत).
- नियमानुसार उपरोक्त कागदपत्रे आणि तांत्रिकबाबी असलेला पहिला लिफाफा उघडण्यात येईल. सर्व कागदपत्रे आणि विभागाच्या तांत्रिक बाबींची पूर्तता करणाऱ्या पुरवठाधारकांचा दर नमूद असलेला दुसरा लिफाफा उघडण्यात येईल.
- पात्र पुरवठाधारकांच्या कंपनीची प्रत, साहित्य कोणत्या कंपनीचे आहे, त्याची गुणवत्ता/दर्जा, विद्यापीठास सेवा दिलेली असल्यास समानधाकारक आहे किंवा नाही, या सर्व बाबींचा विचार करून साहित्य खरेदीची पुढील प्रक्रिया करण्यात येईल
- फक्त ब्रॅन्डेड कंपनीचेच दर नमूद केलेले असावेत. लोकल मेड किंवा असेम्बल केल्या जाणाऱ्या साहित्याचा खरेदी/सेवा देखभाल दुरुस्तीकरीता प्राप्त दरपत्रकांचा विचार केला जाणार नाही.
- अधिकृत विक्रेता, अधिकृत वितरक, मुळ उत्पादक, लघु उद्योजक यांनी संबंधीत कागदपत्रे तांत्रिक लिफाफ्यासोबत सादर करावीत.
- पात्र पुरवठाधारकांनी सादर केलेले दर आणि प्रचलित बाजार दर तपासून सर्वात कमी (L₁) दर नमूद करणाऱ्या पुरवठाधारकांसोबत दरवाटाघाटी करण्यात येतील.
- दरवाटाघाटी नंतर अंतिम ठरलेल्या पुरवठाधारकांस रु. १ लक्ष वरील खरेदीसाठी आदेशप्रपत्र देण्यापूर्वी (As per Accounts Code 5.44) ५ % सुरक्षा ठेव (Security Deposit) ०१ वर्षाच्या कालावधी करीता वित्त व लेखा विभागात जमा करावी लागेल.
- रु. २.५० लक्ष वरील खरेदी, सेवा व देखभाल दुरुस्तीसाठी शासन निर्णयानुसार GST TDS 2% कपात केला जाईल असा उल्लेख दरमागणीपत्रात करण्यात यावा.


कार्यकारी अभियंता

